

Electrical Characteristics :
 Insulation Resistance : 500MΩ Min.
 Contact Resistance : 50mΩ Max.
 Withstand Voltage : 1000 VAC 1 minute.
 Current Rating : 1.5A


Material:
 Housing: Thermoplastic UL 94V-0
 Contact : Selective Gold Plating
 Terminal: 0.35mm Thickness Phosphor Bronze
 Plated With Gold And Tin In Solder Area.
 CUL File No : E215573

PART NO : 5 3 6 6 C - B * 1

Positions →
 Contacts →
 Housing Color →
 B : Black

Ports →
 Gold Plated
 0 : Gold Flash
 1 : 6u"
 2 : 15u"
 3 : 30u"
 4 : 50u"

 **CHAMPWAY** 冠泰電子有限公司
 CHAMPWAY ELECTRONICS CO., LTD.

ZONE	REV.	DESCRIPTION	DATE	APPD.	FILE NO : 5366C (SERIES)	TITLE	NON SHIELDED RJ11 TOP ENTRY PCB JACK		UNIT	mm	
(A)	A.1	Withstand Voltage 500修改為1000VAC	2008-08-01	Nick	TOLERANCE(公差) : 0.000 mm ± 0.075 mm 0.00 mm ± 0.15 mm 0.0 mm ± 0.25 mm	圖名	5366C-B*1		單位	inch	
(B)						PART NO.	5366C-B*1		SCALE	1:1	
(C)						REV.	A.1	DATE	2007-11-20		
(D)						版本		日期			
(E)						CHECKED BY	Michael		DRAWN BY	David	
						審核			製圖		